Python For Loops

Python For Loops

A for loop is used for iterating over a sequence (that is either a list, a tuple, a dictionary, a set, or a string).

This is less like the for keyword in other programming languages, and works more like an iterator method as found in other object-orientated programming languages.

With the for loop we can execute a set of statements, once for each item in a list, tuple, set etc.

Example

Print each fruit in a fruit list:

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    print(x)
```

The for loop does not require an indexing variable to set beforehand.

Looping Through a String

Even strings are iterable objects, they contain a sequence of characters:

Example

Loop through the letters in the word "banana":

```
for x in "banana":
    print(x)
```

The break Statement

With the break statement we can stop the loop before it has looped through all the items:

Example

Exit the loop when x is "banana":
fruits = ["apple", "banana", "cherry"]
for x in fruits:
 print(x)
 if x == "banana":
 break

Example

Exit the loop when \mathbf{x} is "banana", but this time the break comes before the print:

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    if x == "banana":
        break
    print(x)
```

The continue Statement

With the continue statement we can stop the current iteration of the loop, and continue with the next:

Example

Do not print banana: fruits = ["apple", "banana", "cherry"] for x in fruits: if x == "banana": continue print(x)

The range() Function

To loop through a set of code a specified number of times, we can use the range () function,

The range() function returns a sequence of numbers, starting from 0 by default, and increments by 1 (by default), and ends at a specified number.

Example

Using the range() function:

```
for x in range(6):
    print(x)
```

Note that range (6) is not the values of 0 to 6, but the values 0 to 5.

The range() function defaults to 0 as a starting value, however it is possible to specify the starting value by adding a parameter: range(2, 6), which means values from 2 to 6 (but not including 6):

Example

Using the start parameter:

```
for x in range(2, 6):
    print(x)
```

The range() function defaults to increment the sequence by 1, however it is possible to specify the increment value by adding a third parameter: range(2, 30, 3):

Example

Increment the sequence with 3 (default is 1):

```
for x in range(2, 30, 3):
    print(x)
```

Else in For Loop

The else keyword in a for loop specifies a block of code to be executed when the loop is finished:

Example

Print all numbers from 0 to 5, and print a message when the loop has ended:

```
for x in range(6):
```

print(x)

else:

```
print("Finally finished!")
```

Note: The else block will NOT be executed if the loop is stopped by a break statement.

Example

Break the loop when x is 3, and see what happens with the else block:

```
for x in range(6):
    if x == 3: break
        print(x)
    else:
        print("Finally finished!")
```

Nested Loops

A nested loop is a loop inside a loop.

The "inner loop" will be executed one time for each iteration of the "outer loop":

Example

Print each adjective for every fruit:

```
adj = ["red", "big", "tasty"]
fruits = ["apple", "banana", "cherry"]
for x in adj:
    for y in fruits:
```

The pass Statement

for loops cannot be empty, but if you for some reason have a for loop with no content, put in the pass statement to avoid getting an error.

Example

for x in [0, 1, 2]:

pass